



NovaFount FS-507

One-Step Fountain Solution for Sheetfed Presses

Description

NovaFount FS-507 is a one-step fountain solution formulated for use on manroland sheetfed presses. Fogra approval is pending. This product is suited for all types of continuous dampening systems in heatset web offset. It is formulated to reduce the need for alcohol and may even totally eliminate such a need.

Directions

Fill the dampening system with water, add 4-6 oz./gal. of NovaFount FS-507.

Product Need and Usage

NovaFount FS 507 is formulated to meet the requirements for manroland sheetfed presses. Requirements include that it is non-corrosive and non-damaging to bearings, cylinders and other metal parts. It will provide stable ink/water balance, consistent print quality, and no over-emulsification with minimum dampening feed. NovaFount FS-507 provides excellent plate protection and will reduce blanket piling and blanket washing requirements.

Features

- * Fogra qualified for manroland (pending).
- * Non-corrosive.
- * Stable ink-water balance.
- * Consistent print quality.
- * Excellent plate protection.

Technical Specifications

VOC (lb/gal method 24)	1.75
Specific Gravity	1.075
pH	4.65
Dosage	4 to 6 oz./gal.
Color	Amber

Rev. 2/12/2009

Disclaimer: Unless otherwise restricted by applicable law, nothing contained in this literature shall be deemed a representation or warranty of any kind, either expressed or implied. See the Material Safety Data Sheets (MSDS) for this product for safety information prior to use.