



NovaFount FS-675

Mild Acid Fountain Solution

Description

NovaFount FS-675 is a mild acid fountain solution for web offset lithography. Fogra approval pending.

Directions

Use one to three ounces per gallon as needed. Suggested mix is two ounces per gallon.

Product Need and Usage

NovaFount FS-675 is formulated to meet the needs of newspaper printing. It is formulated for use on "Turbo" and other dampening systems.

Features

- * Provides fast start-ups.
- * Protects and restores plate surfaces.
- * Excellent protection from fungus organisms.
- * Promotes stable ink/water balance.
- * Fogra compliant formulation.

Technical Specifications

VOC (lb/gal method 24)	0.48
Specific Gravity	1.065
pH	4.8
Dosage	1 to 3 oz./gal.
Color	Clear, colorless

Rev. 5/10/2011

Disclaimer: Unless otherwise restricted by applicable law, nothing contained in this literature shall be deemed a representation or warranty of any kind, either expressed or implied. See the Material Safety Data Sheets (MSDS) for this product for safety information prior to use.

Nova Pressroom Products LLC
1663 North McDuff Avenue, Jacksonville, FL 32254 | PO Box 2700, Jacksonville, FL 32203
toll-free: 866.443.5811 tel: 904.292.2554 fax: 904.292.2665
www.novapressroom.com