

SAFETY DATA SHEET

WORKING COPY



Date Prepared : 2/23/2015
SDS No : N-333F

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: FOGRA Approved Blanket and Roller Wash

PRODUCT CODE: N-333F

MANUFACTURER

Nova Pressroom Products
1663 North McDuff Avenue
Jacksonville, FL 32254

Alternate Emergency Phone: (866) 443-5811

Customer Service: (904) 292-2554

Transportation: (800) 424-9300

24 HR. EMERGENCY TELEPHONE NUMBERS

Poison Control Center (Medical) : (877) 800-5553

CANUTEC (Canadian Transportation) : (613) 996-6666

CHEMTREC (US Transportation) : (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 5
Skin Irritation, Category 3
Eye Irritation, Category 2B
Respiratory Tract Irritation, Category 3

Physical:

Flammable Liquids, Category 4

GHS LABEL

Combustible Liquid



Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H227: Combustible liquid.
H303: May be harmful if swallowed.
H316: Causes mild skin irritation.
H320: Causes eye irritation.
H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P210: Keep away from heat, sparks, open flames and hot surfaces. – No smoking.
P261: Avoid breathing fumes, mist or vapors.

P264: Wash hands thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves and eye protection.

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378: In case of fire: Use dry chemical for extinction.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.
P233: Keep container tightly closed.

Disposal:

P501: Dispose of contents and container in accordance with local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Blue liquid with solvent odor

IMMEDIATE CONCERNS: Can cause eye, skin or respiratory tract irritation. Can cause severe lung damage and may be fatal if swallowed. May cause CNS depression. Combustible. Vapors are heavier than air and may travel across the ground and reach remote ignition sources causing a flashback fire. During emergencies, wear equipment to protect eyes, skin and respiratory tract. Dike or absorb spills to keep material and run-off from entering sewers, drains or waterways.

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

SKIN: Prolonged or repeated contact with liquid can cause defatting and drying of the skin, and can lead to irritation and/or dermatitis.

SKIN ABSORPTION: May be harmful if absorbed through skin.

INGESTION: May cause nausea, vomiting, diarrhea; possible chemical pneumonitis if aspirated into lungs.

INHALATION: Irritating to the respiratory tract. May cause headache, dizziness, anesthetic effects (CNS depression). Breathing high concentrations in an enclosed space or by intentional abuse can cause irregular heartbeats, which can cause death.

MEDICAL CONDITIONS AGGRAVATED: Significant chronic exposure may aggravate existing eye, skin, respiratory system, liver, kidney, and CNS conditions.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Solvent Naphtha (petroleum), Medium Aliphatic	90 - 100	64742-88-7

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. If irritation persists, seek medical attention.

SKIN: Remove contaminated clothing; launder before re-use. Wash skin with soap and water. If irritation develops or persists, seek medical attention.

INGESTION: Seek immediate medical advice. Do NOT induce vomiting, do NOT drink water.

INHALATION: Remove person to fresh air. If breathing becomes difficult, seek medical attention.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Category 4 - Combustible Liquid

EXTINGUISHING MEDIA: Foam, dry chemical; use water spray to cool exposed surfaces. Evacuate area and fight fire from a safe distance if fire is contained in a small area; otherwise, call the local fire department. Fire media runoff may damage the environment. Dike and collect media used to fight fire.

OTHER CONSIDERATIONS: Vapors are heavier than air and may accumulate in low or inadequately ventilated areas. Vapors may travel along the ground to be ignited at locations distant from the handling site. Flashback or flame to the handling site may

occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire may produce hazardous fumes.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear protective gloves and eye protection, and stop the source of the leak or spill if possible. Isolate area of spill with dike, and/or add dry absorbent to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

LARGE SPILL: Follow OSHA emergency response regulations and NIOSH recommendations. If possible, stop source of spill or release. Isolate the area of spill or release with dike to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes, skin, or clothing. Avoid breathing mist or vapor. Do not swallow. Wash hands thoroughly after handling. Do not eat, drink, or smoke in work areas. Use only with adequate ventilation. Avoid using in areas with open flames, welding arcs, extreme heat or sparks.

STORAGE: Store in a cool, dry, well-ventilated area. Keep container closed when not in use. Transfer to bonded and grounded containers only. Avoid storage with acids/bases and strong oxidizers. Containers of this material may be hazardous when emptied. Because emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this data sheet must be observed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Good, general ventilation should be sufficient for most operations. Ten or more room air changes per hour containing a minimum of 15% fresh air is recommended.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses.

SKIN: Gloves impervious to the hazardous ingredients.

RESPIRATORY: If used under normal operating conditions and with adequate ventilation, respiratory equipment is not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild solvent odor

ODOR THRESHOLD: Not Established

COLOR: Blue

pH: NA = Not Applicable

FLASH POINT AND METHOD: ~ (145°F) CC

FLAMMABLE LIMITS: Not established

AUTOIGNITION TEMPERATURE: Not Established

VAPOR PRESSURE: 0.5 mmHg at 20°C

VAPOR DENSITY: Not Established

BOILING POINT: (310°F) to (380°F)

FREEZING POINT: Not Established

SOLUBILITY IN WATER: 100% Miscible

EVAPORATION RATE: Not Established

DENSITY: Not Established

SPECIFIC GRAVITY: 0.792 at (77°F)

Notes: Water = 1.00

VISCOSITY: Not Established

(VOC): 6.260 lbs/gal USEPA Method 24

COEFF. OIL/WATER: Not Established

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: No

STABILITY: Chemically stable

CONDITIONS TO AVOID: High temperatures, localized heat sources (i.e.: drum or band heaters), oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing, strong oxidizers, strong reducers, free radical initiators, inert gases, oxygen scavengers.

HAZARDOUS DECOMPOSITION PRODUCTS: Includes, but not limited to smoke, fumes, oxides of nitrogen, and oxides of carbon.

INCOMPATIBLE MATERIALS: Strong oxidizers, acids, and/or bases.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀	INHALATION LC ₅₀
Solvent Naphtha (petroleum), Medium Aliphatic	25000	> 4000	> 700

EYES: May cause eye irritation.

SKIN ABSORPTION: May cause skin irritation.

ORAL LD₅₀: Not Established

INHALATION LC₅₀: May cause respiratory tract irritation.

CHRONIC: Prolonged or repeated skin contact may cause dermatitis and/or sensitization. Chronic overexposure to aliphatic petroleum distillates has been found to cause kidney damage in male rats. The mechanism by which this toxicity occurs is specific to the male rat and the kidney effects are not expected to occur in humans. Reports have associated repeated and prolonged overexposure to solvents with irreversible brain and nervous system damage, sometimes referred to as "Solvent or Painter's Syndrome." Overexposure to the aromatic petroleum distillate (or its components) has been suggested as a cause of the following effects in laboratory animals: mild, reversible liver effects; mild, reversible kidney effects; and blood abnormalities. Overexposure to the aromatic petroleum distillate (or its components) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain. The aromatic petroleum distillate may contain trace amounts of Naphthalene. The International Agency for Research on Cancer (IARC) evaluated Naphthalene and concluded that there was sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Accordingly, IARC classified Naphthalene as a possible human carcinogen (Group 2B). The U.S. National Toxicology Program (NTP) has evaluated Naphthalene and found that it may be reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Not Available

BIOACCUMULATION/ACCUMULATION: Not Available

CHEMICAL FATE INFORMATION: Not Available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose materials associated with cleaning spills and/or leaks according to federal, state, and local regulations. If product is contaminated with other printing process products, consult appropriate federal, state, and local regulations to determine proper characterization of resultant mixture.

RCRA/EPA WASTE INFORMATION: None

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Combustible liquid, N.O.S. (Petroleum distillates)

UN/NA NUMBER: 1993

PACKING GROUP: III

NAERG: 128

OTHER SHIPPING INFORMATION: for bulk shipments (>119 gallons); less than bulk quantities are not regulated.

AIR (ICAO/IATA)

SHIPPING NAME: Not Available

VESSEL (IMO/IMDG)

SHIPPING NAME: Not Available

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: This product does not contain any ingredients subject to the reporting requirements of SARA Title III Section 313 at or above reporting thresholds, unless listed below.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All components of this product are registered on the TSCA inventory.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Class D2B Toxic Material

WHMIS CLASS: Class B Combustible Material

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are registered on the DSL inventory.

16. OTHER INFORMATION


APPROVED BY: HRB **TITLE:** VP Technical Services

PREPARED BY: RAD - EHS Manager **Date Prepared:** 2/23/2015

HMIS RATING

HEALTH	<input type="checkbox"/>	1
FLAMMABILITY	<input type="checkbox"/>	2
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	B

NFPA CODES



MANUFACTURER DISCLAIMER:

The specific chemical identities of some ingredients in this mixture are considered proprietary information and trade secrets. As such they are withheld in accordance with CFR 1910.1200(i) of Title 29.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. Some information may be based on indirect test data.