

SAFETY DATA SHEET

WORKING COPY



Date Prepared : 3/2/2015
SDS No : N-350UVA

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: Blanket and Roller Wash for Hybrid Inks

PRODUCT CODE: N-350UVA

MANUFACTURER

Nova Pressroom Products
1663 North McDuff Avenue
Jacksonville, FL 32254

Alternate Emergency Phone: (866) 443-5811

Customer Service: (904) 292-2554

Transportation: (800) 424-9300

24 HR. EMERGENCY TELEPHONE NUMBERS

Poison Control Center (Medical) : (877) 800-5553

CANUTEC (Canadian Transportation) : (613) 996-6666

CHEMTREC (US Transportation) : (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Oral), Category 5
Skin Irritation, Category 3
Eye Irritation, Category 2B
Respiratory Tract Irritation, Category 3

Physical:

Flammable Liquids, Category 4

GHS LABEL

Flammable Liquid and Vapor



Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H227: Combustible liquid.
H303: May be harmful if swallowed.
H316: Causes mild skin irritation.
H320: Causes eye irritation.
H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENTS

Prevention:

P210: Keep away from heat, sparks, open flames and hot surfaces. – No smoking.
P233: Keep container tightly closed.

P241: Use explosion-proof electrical equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing fumes, mist or vapors.
P264: Wash hands thoroughly after handling.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves and eye protection.

Response:

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P370+P378: In case of fire: Use dry chemical for extinction.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.
P233: Keep container tightly closed.

Disposal:

P501: Dispose of contents and container in accordance with local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear, colorless liquid with mild solvent odor.

IMMEDIATE CONCERNS: Can cause eye, skin or respiratory tract irritation. Can cause severe lung damage and may be fatal if swallowed. May cause CNS depression. Combustible. Vapors are heavier than air and may travel across the ground and reach remote ignition sources causing a flashback fire. During emergencies, wear equipment to protect eyes, skin and respiratory tract. Dike or absorb spills to keep material and run-off from entering sewers, drains or waterways.

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

SKIN: Prolonged or repeated contact with liquid can cause defatting and drying of the skin, and can lead to irritation and/or dermatitis.

SKIN ABSORPTION: May be harmful if absorbed through skin.

INGESTION: May cause nausea, vomiting, diarrhea; possible chemical pneumonitis if aspirated into lungs.

INHALATION: Irritating to the respiratory tract. May cause headache, dizziness, anesthetic effects (CNS depression). Breathing high concentrations in an enclosed space or by intentional abuse can cause irregular heartbeats, which can cause death.

MEDICAL CONDITIONS AGGRAVATED: Significant chronic exposure may aggravate existing eye, skin, respiratory system, liver, kidney, and CNS conditions.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Dipropylene Glycol Methyl Ether	70 - 80	34590-94-8

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. If irritation persists, seek medical attention.

SKIN: Remove contaminated clothing; launder before re-use. Wash skin with soap and water. If irritation develops or persists, seek medical attention.

INGESTION: Seek immediate medical advice. Do NOT induce vomiting, do NOT drink water.

INHALATION: Remove person to fresh air. If breathing becomes difficult, seek medical attention.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Category 4 - Combustible Liquid

EXTINGUISHING MEDIA: Foam, dry chemical; use water spray to cool exposed surfaces. Evacuate area and fight fire from a safe distance if fire is contained in a small area; otherwise, call the local fire department. Fire media runoff may damage the environment. Dike and collect media used to fight fire.

OTHER CONSIDERATIONS: Vapors are heavier than air and may accumulate in low or inadequately ventilated areas. Vapors may travel along the ground to be ignited at locations distant from the handling site. Flashback or flame to the handling site may occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire may produce hazardous fumes.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear protective gloves and eye protection, and stop the source of the leak or spill if possible. Isolate area of spill with dike, and/or add dry absorbent to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

LARGE SPILL: Follow OSHA emergency response regulations and NIOSH recommendations. If possible, stop source of spill or release. Isolate the area of spill or release with dike to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes, skin, or clothing. Avoid breathing mist or vapor. Do not swallow. Wash hands thoroughly after handling. Do not eat, drink, or smoke in work areas. Use only with adequate ventilation. Avoid using in areas with open flames, welding arcs, extreme heat or sparks.

STORAGE: Store in a cool, dry, well-ventilated area. Keep container closed when not in use. Transfer to bonded and grounded containers only. Avoid storage with acids/bases and strong oxidizers. Containers of this material may be hazardous when emptied. Because emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this data sheet must be observed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
Dipropylene Glycol Methyl Ether	TWA	100	600	100	606
	STEL			150	909

ENGINEERING CONTROLS: Good, general ventilation should be sufficient for most operations. Ten or more room air changes per hour containing a minimum of 15% fresh air is recommended.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses.

SKIN: Gloves impervious to the hazardous ingredients.

RESPIRATORY: If used under normal operating conditions and with adequate ventilation, respiratory equipment is not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild solvent odor

ODOR THRESHOLD: Not Established

APPEARANCE: Clear

COLOR: None

pH: NA = Not Applicable

FLASH POINT AND METHOD: ~ (172°F) TCC
FLAMMABLE LIMITS: Not established
AUTOIGNITION TEMPERATURE: Not Established
VAPOR PRESSURE: 0.35 mmHg at 20°C
VAPOR DENSITY: Not Established
BOILING POINT: (310°F) to (380°F)
FREEZING POINT: Not Established
SOLUBILITY IN WATER: 100% Miscible
EVAPORATION RATE: Not Established
DENSITY: Not Established
SPECIFIC GRAVITY: 0.78 to 0.80 at (77°F)
Notes: Water = 1.00
VISCOSITY: Not Established
(VOC): 7.900 lbs/gal USEPA Method 24
COEFF. OIL/WATER: Not Established

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: No

STABILITY: Chemically stable

CONDITIONS TO AVOID: High temperatures, localized heat sources (i.e.: drum or band heaters), oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing, strong oxidizers, strong reducers, free radical initiators, inert gases, oxygen scavengers.

HAZARDOUS DECOMPOSITION PRODUCTS: Includes, but not limited to smoke, fumes, oxides of nitrogen, and oxides of carbon.

INCOMPATIBLE MATERIALS: Strong oxidizers, acids, and/or bases.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀
Dipropylene Glycol Methyl Ether	5350 mg/kg [Rat]	9500 mg/kg [Rabbit]

EYES: May cause eye irritation.

SKIN ABSORPTION: May cause skin irritation.

ORAL LD₅₀: Not Established

INHALATION LC₅₀: May cause respiratory tract irritation.

CHRONIC: Chronic overexposure to Dipropylene Glycol Monomethyl Ether has been suggested as a cause of mild, reversible liver effects in laboratory animals.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Not Available

BIOACCUMULATION/ACCUMULATION: Not Available

CHEMICAL FATE INFORMATION: Not Available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose materials associated with cleaning spills and/or leaks according to federal, state, and local regulations. If product is contaminated with other printing process products, consult appropriate federal, state, and local

regulations to determine proper characterization of resultant mixture.

RCRA/EPA WASTE INFORMATION: D001 (Ignitable Characteristic)

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Combustible liquid, N.O.S. (Dipropylene Glycol Monomethyl Ether)

UN/NA NUMBER: 1993

PACKING GROUP: III

NAERG: 128

OTHER SHIPPING INFORMATION: for bulk shipments (>119 gallons); less than bulk quantities are not regulated.

AIR (ICAO/IATA)

SHIPPING NAME: None

VESSEL (IMO/IMDG)

SHIPPING NAME: None

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: This product does not contain any ingredients subject to the reporting requirements of SARA Title III Section 313 at or above reporting thresholds, unless listed below.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All components of this product are registered on the TSCA inventory.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Class D2B Toxic Material

WHMIS CLASS: Class B Combustible Material

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are registered on the DSL inventory.

16. OTHER INFORMATION


APPROVED BY: HRB **TITLE:** VP Technical Services

PREPARED BY: RAD - EHS Manager **Date Prepared:** 3/2/2015

HMIS RATING

HEALTH	*	1
FLAMMABILITY		2
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

NFPA CODES



MANUFACTURER DISCLAIMER:

The specific chemical identities of some ingredients in this mixture are considered proprietary information and trade secrets. As such they are withheld in accordance with CFR 1910.1200(i) of Title 29.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. Some information may be based on indirect test data.