



### ECONOMY SOFT TOUCH UV

#### DESCRIPTION:

NOVACURE-7999 is a economic UV soft touch matte coating and can be used as a overprint for tactile effect on paper and board substrates. NOVACURE-7999 is a low viscosity product and the tactile effect can be increased based on volume of coating applied. It is formulated for economic versatility. NOVACURE-7999 derives a soft tactile effect and is formulated for more disposable type products that extreme long term durability or high end tactile effect is not required. Wider and shallow anilox cells are required for best effect and distribution. For longer soft touch duration on finished product, better durability and faster curing use NC-7900. This product must be mixed prior to every use.

#### INK HANDLING:

**MIX WELL BEFORE USE.** Direct skin contact to UV coatings is the primary route of exposure and irritation. Therefore, it is recommended that all personnel handling UV products wear gloves and barrier cream to prevent direct skin contact. Safety glasses are suggested in areas where coating may be splashed. If coating does come in contact with skin, wipe it off with a clean, dry cloth (do not use solvent or reducer). Wash the affected area with soap and water. Consult the Safety Data Sheets for further instructions and warnings.

#### STORAGE:

Store tightly covered at temperatures between 65-90°F. Coating taken from the press should not be returned to the original container. Store separately to avoid contamination.

#### FEATURES:

- Soft and Velvet feel
- Economically priced
- Good rub resistance
- Versatile use
- Low viscosity
- Silicone free

#### APPLICATIONS:

- Roller
- Anilox
- Flexo
- Narrow Web
- Screenprint

#### TECHNICAL SPECIFICATIONS:

Flash Point (*F TCC)	> 200
Specific Gravity	1.08
Color	Colorless
Solids	100%
Gluing, Stamping	Test First due to variety of glues and foils
Viscosity	200-300 @ 60 RPM and 77°F/23°C
Cure Speed	100 feet per minute with a 300 watt bulb
Flammability	No
Shelf Life	3 months

Nova Pressroom Products, LLC  
1663 McDuff Ave N  
Toll-Free: 866-443-5811  
Tel: 904-292-2554  
Fax: 904-389-6999  
[www.novapressroom.com](http://www.novapressroom.com)

#### VERIFICATION OF SUITABILITY: SDS'S ARE AVAILABLE ONLINE AT NOVAPRESSROOM.COM OR CALL 904-292-2554 x22.

After press/job set-up is complete, inspect a portion of the printed web for all applicable and specified properties. These properties include but are not limited to: cure, adhesion, mar and rub resistance, product resistance, gloss, and coefficient of friction. These tests should be performed prior to beginning the full production run.

\*Performance specifications will vary depending on substrate, ink used, lamps, and coating film weight.

Disclaimer: Unless otherwise restricted by applicable law, nothing contained in this literature shall be deemed a representation or warranty of any kind, either expressed or implied. See the Safety Data Sheets (SDS) for this product for safety information prior to use.

SIZES AVAILABLE: 5 gal, 55 gal, or 275 gal