

# SAFETY DATA SHEET

WORKING COPY



Date Prepared : 3/9/2015  
SDS No : SP-117

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT DESCRIPTION:** VOC Exempt Metering Roller Cleaner

**PRODUCT CODE:** SP-117

### MANUFACTURER

Nova Pressroom Products  
1663 North McDuff Avenue  
Jacksonville, FL 32254

**Alternate Emergency Phone:** (866) 443-5811

**Customer Service:** (904) 292-2554

**Transportation:** (800) 424-9300

### 24 HR. EMERGENCY TELEPHONE NUMBERS

**Poison Control Center (Medical) :** (877) 800-5553

**CANUTEC (Canadian Transportation) :** (613) 996-6666

**CHEMTREC (US Transportation) :** (800) 424-9300

## 2. HAZARDS IDENTIFICATION

### GHS CLASSIFICATIONS

#### Health:

Acute Toxicity (Oral), Category 5  
Skin Irritation, Category 3  
Eye Irritation, Category 2B  
Respiratory Tract Irritation, Category 3

#### Physical:

Flammable Liquids, Category 2

### GHS LABEL

Highly Flammable Liquid and Vapor



Flame



Exclamation  
mark

**SIGNAL WORD:** DANGER

### HAZARD STATEMENTS

H225: Highly flammable liquid and vapor.  
H303: May be harmful if swallowed.  
H316: Causes mild skin irritation.  
H320: Causes eye irritation.  
H335: May cause respiratory irritation.

### PRECAUTIONARY STATEMENTS

#### Prevention:

P210: Keep away from heat, sparks, open flames and hot surfaces. – No smoking.  
P233: Keep container tightly closed.

P241: Use explosion-proof electrical equipment.  
P242: Use only non-sparking tools.  
P243: Take precautionary measures against static discharge.  
P261: Avoid breathing fumes, mist or vapors.  
P264: Wash hands thoroughly after handling.  
P271: Use only outdoors or in a well-ventilated area.  
P280: Wear protective gloves and eye protection.

**Response:**

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P370+P378: In case of fire: Use dry chemical for extinction.

**Storage:**

P403+P235: Store in a well-ventilated place. Keep cool.  
P233: Keep container tightly closed.

**Disposal:**

P501: Dispose of contents and container in accordance with local regulations.

**EMERGENCY OVERVIEW**

**PHYSICAL APPEARANCE:** Clear, colorless liquid with strong acetone odor.

**IMMEDIATE CONCERNS:** Can cause eye, skin or respiratory tract irritation. Can cause severe lung damage and may be fatal if swallowed. May cause CNS depression. Extremely flammable liquid and vapor. May cause flash fire. Vapors are heavier than air and may travel across the ground and reach remote ignition sources causing a flashback fire. During emergencies, wear equipment to protect eyes, skin and respiratory tract. Dike or absorb spills to keep material and run-off from entering sewers, drains or waterways.

**POTENTIAL HEALTH EFFECTS**

**EYES:** Contact may cause eye irritation.

**SKIN:** Prolonged or repeated contact with liquid can cause defatting and drying of the skin, and can lead to irritation and/or dermatitis.

**SKIN ABSORPTION:** May be harmful if absorbed through skin.

**INGESTION:** May cause nausea, vomiting, diarrhea; possible chemical pneumonitis if aspirated into lungs.

**INHALATION:** Irritating to the respiratory tract. May cause headache, dizziness, anesthetic effects (CNS depression). Breathing high concentrations in an enclosed space or by intentional abuse can cause irregular heartbeats, which can cause death.

**MEDICAL CONDITIONS AGGRAVATED:** Significant chronic exposure may aggravate existing eye, skin, respiratory system, liver, kidney, and CNS conditions.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Chemical Name	Wt.%	CAS
Acetone	80 - 90	67-64-1
N-heptane	10 - 20	142-82-5
2- Butoxyethanol	< 5	111-76-2

**4. FIRST AID MEASURES**

**EYES:** Immediately flush eyes with plenty of water. If irritation persists, seek medical attention.

**SKIN:** Remove contaminated clothing; launder before re-use. Wash skin with soap and water. If irritation develops or persists, seek medical attention.

**INGESTION:** Seek immediate medical advice. Do NOT induce vomiting, do NOT drink water.

**INHALATION:** Remove person to fresh air. If breathing becomes difficult, seek medical attention.

## 5. FIRE FIGHTING MEASURES

**FLAMMABLE CLASS:** Category 2 - Highly Flammable Liquid and Vapor

**EXTINGUISHING MEDIA:** Foam, dry chemical; use water spray to cool exposed surfaces. OSHA Class IB Flammable Liquid.

Evacuate area and fight fire from a safe distance if fire is contained in a small area; otherwise, call the local fire department. Fire media runoff may damage the environment. Dike and collect media used to fight fire.

**OTHER CONSIDERATIONS:** Vapors are heavier than air and may accumulate in low or inadequately ventilated areas. Vapors may travel along the ground to be ignited at locations distant from the handling site. Flashback or flame to the handling site may occur.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Fire may produce hazardous fumes.

## 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Wear protective gloves and eye protection, and stop the source of the leak or spill if possible. Isolate area of spill with dike, and/or add dry absorbent to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

**LARGE SPILL:** Follow OSHA emergency response regulations and NIOSH recommendations. If possible, stop source of spill or release. Isolate the area of spill or release with dike to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

## 7. HANDLING AND STORAGE

**HANDLING:** Avoid contact with eyes, skin, or clothing. Avoid breathing mist or vapor. Do not swallow. Wash hands thoroughly after handling. Do not eat, drink, or smoke in work areas. Use only with adequate ventilation. Avoid using in areas with open flames, welding arcs, extreme heat or sparks.

**STORAGE:** Store in a cool, dry, well-ventilated area. Keep container closed when not in use. Transfer to bonded and grounded containers only. Avoid storage with acids/bases and strong oxidizers. Containers of this material may be hazardous when emptied. Because emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this data sheet must be observed.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Acetone	TWA	1000	2400	500	
	STEL			750	
N-heptane	TWA	500	2000	400	
	STEL			500	
2- Butoxyethanol	TWA	50	240	20	97

**ENGINEERING CONTROLS:** Good, general ventilation should be sufficient for most operations. Ten or more room air changes per hour containing a minimum of 15% fresh air is recommended.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety glasses.

**SKIN:** Gloves impervious to the hazardous ingredients.

**RESPIRATORY:** If used under normal operating conditions and with adequate ventilation, respiratory equipment is not required.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid  
**ODOR:** Strong solvent odor  
**ODOR THRESHOLD:** Not Established  
**APPEARANCE:** Clear  
**COLOR:** None  
**pH:** NA = Not Applicable  
**FLASH POINT AND METHOD:** ~ (1°F) TCC  
**FLAMMABLE LIMITS:** Not established  
**AUTOIGNITION TEMPERATURE:** Not Established  
**VAPOR PRESSURE:** 0.1 mmHg at 20°C  
**VAPOR DENSITY:** Not Established  
**BOILING POINT:** (130°F) to (340°F)  
**FREEZING POINT:** Not Established  
**SOLUBILITY IN WATER:** 100% Miscible  
**EVAPORATION RATE:** Not Established  
**DENSITY:** Not Established  
**SPECIFIC GRAVITY:** 0.792 at (77°F)  
**Notes:** Water = 1.00  
**VISCOSITY:** Not Established  
**(VOC):** 0.810 lbs/gal USEPA Method 24  
**COEFF. OIL/WATER:** Not Established

## 10. STABILITY AND REACTIVITY

**HAZARDOUS POLYMERIZATION:** No  
**STABILITY:** Chemically stable  
**CONDITIONS TO AVOID:** High temperatures, localized heat sources (i.e.: drum or band heaters), oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing, strong oxidizers, strong reducers, free radical initiators, inert gases, oxygen scavengers.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Includes, but not limited to smoke, fumes, oxides of nitrogen, and oxides of carbon.  
**INCOMPATIBLE MATERIALS:** Strong oxidizers, acids, and/or bases.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE

**EYES:** May cause eye irritation.  
**SKIN ABSORPTION:** May cause skin irritation.  
**ORAL LD<sub>50</sub>:** Not Established  
**INHALATION LC<sub>50</sub>:** May cause respiratory tract irritation.

**CHRONIC:** Prolonged or repeated skin contact may cause allergic reaction and dermatitis. Chronic overexposure to organic solvents has been suggested as a cause of the following effects in laboratory animals: testis damage, kidney damage, liver damage, effects on hearing, respiratory tract damage, cardiac sensitization, and central nervous system damage. Prolonged or repeated exposure to Ethylene Glycol Monobutyl Ether can cause damage to the liver, kidneys, lymphoid system, blood and blood-forming organs.

**TERATOGENIC EFFECTS:** 2-butoxyethanol has shown teratogenic effects in laboratory animals.

## 12. ECOLOGICAL INFORMATION

**ECOTOXICOLOGICAL INFORMATION:** Not Available

**BIOACCUMULATION/ACCUMULATION:** Not Available

**CHEMICAL FATE INFORMATION:** Not Available

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose materials associated with cleaning spills and/or leaks according to federal, state, and local regulations. If product is contaminated with other printing process products, consult appropriate federal, state, and local regulations to determine proper characterization of resultant mixture.

**RCRA/EPA WASTE INFORMATION:** D001 (Ignitable Characteristic)

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Flammable liquid, N.O.S. (Acetone, Heptane)

**UN/NA NUMBER:** 1993

**PACKING GROUP:** II

**NAERG:** 128

#### AIR (ICAO/IATA)

**SHIPPING NAME:** Not Available

#### VESSEL (IMO/IMDG)

**SHIPPING NAME:** Not Available

### 15. REGULATORY INFORMATION

#### UNITED STATES

##### SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

**313 REPORTABLE INGREDIENTS:** This product does not contain any ingredients subject to the reporting requirements of SARA Title III Section 313 at or above reporting thresholds, unless listed below.

##### EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Acetone	80 - 90	67-64-1
2- Butoxyethanol	< 5	111-76-2

##### CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

Chemical Name	Wt.%	CERCLA RQ
Acetone	80 - 90	5,000

##### TSCA (TOXIC SUBSTANCE CONTROL ACT)

**TSCA STATUS:** All components of this product are registered on the TSCA inventory.

#### CANADA

**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** Class D2B Toxic Material

**WHMIS CLASS:** Class B Flammable Material

**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components of this product are registered on the DSL inventory.

### 16. OTHER INFORMATION


**APPROVED BY:** HRB    **TITLE:** VP Technical Services

**PREPARED BY:** RAD - EHS Manager    **Date Prepared:** 3/9/2015

### HMIS RATING

HEALTH	*	1
FLAMMABILITY		3
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

### NFPA CODES



### MANUFACTURER DISCLAIMER:

The specific chemical identities of some ingredients in this mixture are considered proprietary information and trade secrets. As such they are withheld in accordance with CFR 1910.1200(i) of Title 29.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. Some information may be based on indirect test data.