

SAFETY DATA SHEET



Date Prepared : 08/23/2017
SDS No : NC-7500
Date Revised : 08/28/2017
Revision No : 1

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT DESCRIPTION: UV Adhesive High Tack/Medium Viscosity
PRODUCT CODE: NC-7500

MANUFACTURER

Nova Pressroom Products
1663 North McDuff Avenue
Jacksonville, FL 32254
Alternate Emergency Phone: (866) 443-5811
Customer Service: (904) 292-2554
Transportation: (800) 424-9300

24 HR. EMERGENCY TELEPHONE NUMBERS

Poison Control Center (Medical) : (877) 800-5553
CANUTEC (Canadian Transportation) : (613) 996-6666
CHEMTREC (US Transportation) : (800) 424-9300

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Inhalation), Category 4
Skin Irritation, Category 2
Skin Sensitization, Category 1
Reproductive Toxicity, Category 2
Target Organ Toxicity (Single exposure), Category 3
Eye Irritation, Category 2A

GHS LABEL



Exclamation
mark



Health
hazard

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H312: Harmful in contact with skin.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.
H361: Suspected of damaging fertility or the unborn child

PRECAUTIONARY STATEMENTS

Prevention:

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P261: Avoid breathing dust, vapours or spray.
P264: Wash hands thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves.

Response:

P312: Call a POISON CENTER or a doctor if you feel unwell.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313: If eye irritation persists: Get medical attention.
P302+P352: IF ON SKIN: Wash with plenty of water
P310: IF IN EYES: Immediately call a POISON CENTER or doctor.
P308+P313: IF exposed or concerned: Get medical advice/ attention.
P332+P313: If skin irritation occurs: Get medical advice.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P362: Take off contaminated clothing.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Pale amber liquid with mild odor

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause eye irritation.

SKIN: Contact may cause skin irritation.

INGESTION: Ingestion may cause irritation to the gastrointestinal tract.

INHALATION: Inhalation may cause irritation to the respiratory tract.

MEDICAL CONDITIONS AGGRAVATED: Significant chronic exposure may aggravate existing eye, skin, respiratory system, liver, kidney, and CNS conditions.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Proprietary Polyester Resin - 10455	55 - 60	Mixture
2-(2-ethoxyethoxy)ethyl acrylate	20 - 30	7328-17-8
Proprietary Polyester Urethane Acrylate - 10454	10 - 20	mixture
Proprietary Photoinitiator Blend - 10450	< 5	Mixture

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. If irritation persists, seek medical attention.

SKIN: Wash skin with soap and water. If irritation develops or persists, seek medical attention.

INGESTION: Seek immediate medical advice. Do not induce vomiting unless instructed to do so by poison center or physician.

INHALATION: Remove person to fresh air. If breathing becomes difficult, seek medical attention.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: None

EXTINGUISHING MEDIA: Foam, dry chemical; use water spray to cool exposed surfaces. Evacuate area and fight fire from a safe distance if fire is contained in a small area; otherwise, call the local fire department. Fire media runoff may damage the

environment. Dike and collect media used to fight fire.

OTHER CONSIDERATIONS: Vapors are heavier than air and may accumulate in low or inadequately ventilated areas. Vapors may travel along the ground to be ignited at locations distant from the handling site. Flashback or flame to the handling site may occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Fire may produce hazardous fumes.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear protective gloves and eye protection, and stop the source of the leak or spill if possible. Isolate area of spill with dike, and/or add dry absorbent to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

LARGE SPILL: Follow OSHA emergency response regulations and NIOSH recommendations. If possible, stop source of spill or release. Isolate the area of spill or release with dike to prevent runoff from entering storm sewers and ditches which lead to waterways. Clean up and place in an appropriate container for disposal. Wash all contaminated clothing before use.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes, skin, or clothing. Avoid breathing mist or vapor. Do not swallow. Wash hands thoroughly after handling. Do not eat, drink, or smoke in work areas. Use only with adequate ventilation. Good housekeeping should be observed to avoid contamination. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used.

STORAGE: Store in a cool, dry, well-ventilated area. Keep container closed when not in use. Keep away from oxidizing agents and corrosives. Protect from direct sunlight and store between 40F and 140F. Containers of this material may be hazardous when emptied. Because emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in this data sheet must be observed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Good, general ventilation should be sufficient for most operations. Ten or more room air changes per hour containing a minimum of 15% fresh air is recommended.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Safety glasses.

SKIN: Gloves impervious to the hazardous ingredients.

RESPIRATORY: If used under normal operating conditions and with adequate ventilation, respiratory equipment is not required.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild odor

APPEARANCE: Clear

COLOR: Pale Amber

pH: NA = Not Applicable

FLASH POINT AND METHOD: > (200°F) CC

FLAMMABLE LIMITS: Not Established

AUTOIGNITION TEMPERATURE: Not Established

VAPOR PRESSURE: Not Established

VAPOR DENSITY: Not Established

BOILING POINT: Not Available

FREEZING POINT: Not Established

THERMAL DECOMPOSITION: Not Established

SOLUBILITY IN WATER: Insoluble

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Established

EVAPORATION RATE: Not Established

DENSITY: Not Established

SPECIFIC GRAVITY: 1.09 at (60°F)

Notes: Water = 1.00

VISCOSITY #1: 1500 to 2000 cps. at (77°F) #2 @ 60

(VOC): < 0.01 lbs/gal USEPA Method 24

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Uncontrollable polymerization of the product with generation of heat can occur above room temperature or if exposed to direct sunlight.

STABILITY: Chemically stable

CONDITIONS TO AVOID: High temperatures, localized heat sources (i.e.: drum or band heaters), oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing, strong oxidizers, strong reducers, free radical initiators, inert gases, oxygen scavengers.

HAZARDOUS DECOMPOSITION PRODUCTS: Includes, but not limited to smoke, fumes, oxides of nitrogen, and oxides of carbon.

INCOMPATIBLE MATERIALS: Rust, strong oxidizers, acids, and/or bases.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀	DERMAL LD ₅₀
Proprietary Polyester Resin - 10455	> 2000 mg/kg [Rat]	
2-(2-ethoxyethoxy)ethyl acrylate	> 500 mg/kg [Rat]	
Proprietary Polyester Urethane Acrylate - 10454	5660 mg/kg [Rat]	8480 mg/kg [Rabbit]
Proprietary Photoinitiator Blend - 10450	> 5000 mg/kg [Rat]	> 2000 mg/kg [Rat]

ORAL LD₅₀: Not Established

INHALATION LC₅₀: May cause respiratory tract irritation.

STOT-REPEATED EXPOSURE: Prolonged or repeated skin contact may cause allergic reaction and dermatitis.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: Not Available

BIOACCUMULATION/ACCUMULATION: Not Available

CHEMICAL FATE INFORMATION: Not Available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose materials associated with cleaning spills and/or leaks according to federal, state, and local regulations. If product is contaminated with other printing process products, consult appropriate federal, state, and local regulations to determine proper characterization of resultant mixture.

RCRA/EPA WASTE INFORMATION: None

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated

AIR (ICAO/IATA)

SHIPPING NAME: Not Regulated

VESSEL (IMO/IMDG)

SHIPPING NAME: Not Regulated

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

313 REPORTABLE INGREDIENTS: This product does not contain any ingredients subject to the reporting requirements of SARA Title III Section 313 at or above reporting thresholds, unless listed below.

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
2-(2-ethoxyethoxy)ethyl acrylate	20 - 30	7328-17-8

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All components of this product are registered on the TSCA inventory.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Class D2B Toxic Material

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are registered on the DSL inventory.

16. OTHER INFORMATION

APPROVED BY: HRB **TITLE:** VP Technical Services


PREPARED BY: RAD - EHS Manager **Date Revised:** 08/28/2017

REVISION SUMMARY: This SDS replaces the 08/23/2017 SDS.

HMIS RATING

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

NFPA CODES



MANUFACTURER DISCLAIMER:

The specific chemical identities of some ingredients in this mixture are considered proprietary information and trade secrets. As such they are withheld in accordance with CFR 1910.1200(i) of Title 29.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. Some information may be based on indirect test data.