



NovaOil 302

High-Grade Oil Lubricant

Description

NovaOil 302 is a high-grade, virgin-base, clinging-type lubricating oil with greater load carrying capability and service life than similar viscosity oils.

Product Need and Usage

NovaOil 302 was developed to meet manufacturer's requirements for a medium-bodied oil that combines high-film strength with good flow characteristics. It provides the perfect combination for both new and old equipment using one-shot lubrication systems and hand-oiling applications.

Features

- * Contains a petroleum-based polymer "clinging" agent that adheres to metal three times longer than ordinary oils.
- * High film strength provides added protection against wear.
- * Proper lubrication with reduced oil consumption as oil is not easily displaced by centrifugal force.
- * Rust inhibitor forms a protective coating that blocks out moisture.
- * Foam inhibitor prevents burned out bearings.
- * Oxidation inhibitor prevents corrosion and minimizes the possibility of gum and sludge formation.

Technical Specifications

Flash Point	228 °C / 442 °F
Pour Point	-33 °C / -27 °F
ISO Viscosity	68
Copper Strip Corrosion Test (ASTM)	Passed
Additives	Rust, Foam and Oxidation Inhibitors plus a Clinging Agent

Rev. 3/3/2008

Disclaimer: Unless otherwise restricted by applicable law, nothing contained in this literature shall be deemed a representation or warranty of any kind, either expressed or implied. See the Material Safety Data Sheets (MSDS) for this product for safety information prior to use.