



NovaFount FS-812

One-Step Alcohol Replacement Fountain Solution

Description

NovaFount FS-812 is a one-step alcohol replacement fountain solution for offset lithography.

Directions

Use seven to nine ounces per gallon of water. Conductivity at eight ounces of water will be 1500 mmhos over the conductivity of the water.

Product Need and Usage

This product is formulated for those who need a one-step fountain solution for use on Heidelberg sheetfed presses, Mitsubishi or Roland web presses, or whenever extra protection from streaking is needed.

Features

- * Stable ink/water balance.
- * Prevents calcium problems.
- * Strong buffering at pH 4.85.
- * Promotes good drying.
- * Excellent protection from growth.

Technical Specifications

VOC (lb/gal method 24)	2.60
Specific Gravity	1.015
pH	4.9
Dosage	7 to 9 oz./gal.
Color	Green

Rev. 1/7/2010

Disclaimer: Unless otherwise restricted by applicable law, nothing contained in this literature shall be deemed a representation or warranty of any kind, either expressed or implied. See the Material Safety Data Sheets (MSDS) for this product for safety information prior to use.

Nova Pressroom Products LLC
1663 North McDuff Avenue, Jacksonville, FL 32254 | PO Box 2700, Jacksonville, FL 32203
toll-free: 866.443.5811 tel: 904.292.2554 fax: 904.292.2665
www.novapressroom.com