



NovaOil M10

High-Grade Circulating Hydraulic Oil

Description

NovaOil M10 is a high-grade, virgin-base hydraulic oil.

Product Need and Usage

NovaOil M10 circulating hydraulic oil contains additives that effectively protect machines against rust, corrosion and oxidation. With the use of this oil, experience has shown that intervals between drain periods may be increased many times over those obtained with straight mineral-type oils. NovaOil M10 has an ISO grade 46 for those applications requiring a light viscosity oil. It is also recommended for certain hydraulic systems and as a circulating hydraulic fluid for small presses.

Features

- * Anti-rust additive forms a protective coating that blocks out moisture.
- * Anti-oxidation additive prevents corrosion and minimizes the possibility of gum and sludge formation.
- * Anti-foam additive eliminates air pockets, ensures full film lubrication and prevents burned out parts.
- * Contains no detergents; not compatible with water.
- * Low pour point; presses start easily in cold.

Technical Specifications

Flash Point	226 °C / 439 °F
Pour Point	-24 °C / -11 °F
ISO Viscosity	46
Copper Strip Corrosion Test (ASTM)	Passed
Additives	Rust, Foam and Oxidation Inhibitors

Rev. 3/3/2008

Disclaimer: Unless otherwise restricted by applicable law, nothing contained in this literature shall be deemed a representation or warranty of any kind, either expressed or implied. See the Material Safety Data Sheets (MSDS) for this product for safety information prior to use.